

Panel Suspended Zenith



BRIGHT AND COMFORTABLE



Bluetooth Control



Dimmable



Flicker Free



Indirect Light



UGR < 19



Uniform Light Colors



Never Fade



Panel Suspended Zenith



Bluetooth Control



Dimmable



Flicker Free



Indirect Light



UGR ≤ 19



Uniform Light Colors



Never Fade

Specification

Item Code	Item Description	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	CRI
542004091700	LEDPanelSp-Z L1222-80W-BLE2-3000-AL	80	8400	105	3000	≤19
542004091800	LEDPanelSp-Z L1222-80W-BLE2-4000-AL	80	8400	105	4000	≤19

Technical Specification	
Life Time (L70B50)	60,000h
On-/Off-Cycles	100000
Colour Consistency (SDCM)	3
Beam Angle	112°up(50%)+down(50%)
Finishing	Aluminum
Colour Rendering Index CRI	≥80
Degree of protection (IP)	IP20
Impact Strength	IK02
Protection Class	II
Glow Wire Test	650°C
Driver Failure Rate (at 5,000 hrs)	<1%
Power Factor	≥0.9

Electrical Supply	
Frequency	50/60Hz
Nominal Voltage	220-240VAC

Mechanical Properties	
Housing Material	Aluminium
Optical Material	PMMA
Cover Material	Semi-opaque PMMA

Application Conditions	
Operating Temperature	-20-45°C
Application Temperature	+25°C
Storage Environment	-25-50°C

Packaging Information

Item		Outer box		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/CTN)
542004091700	LEDPanelSp-Z L1222-80W-BLE2-3000-AL	1332*92*348	5.2	1
542004091800	LEDPanelSp-Z L1222-80W-BLE2-4000-AL	1332*92*348	5.2	1

Dimensional Drawing



Photometric Data

